

MIG welding wire packing / Imballo MIG / MIG emballage / MIG Verpackung

Novametal	Basket spool BS 300 (acc. to EN ISO 544)			Spool S 300 (acc. to EN ISO 544)			Spool S 200 (acc. to EN ISO 544)			Spool S 100 (acc. to EN ISO 544)		
	51.5 (inner Ø)	300.0 (outer Ø)	100.0 (width)	51.5 (inner Ø)	300.0 (outer Ø)	103.0 (width)	50.5 (inner Ø)	200.0 (outer Ø)	55.0 (width)	16.5 (inner Ø)	100.0 (outer Ø)	45.00 (width)
Dimensions (mm)	51.5 (inner Ø)	300.0 (outer Ø)	100.0 (width)	51.5 (inner Ø)	300.0 (outer Ø)	103.0 (width)	50.5 (inner Ø)	200.0 (outer Ø)	55.0 (width)	16.5 (inner Ø)	100.0 (outer Ø)	45.00 (width)
Dimensions (inches)	2.028 (outer Ø)	11.811 (outer Ø)	3.937 (width)	2.028 (inner Ø)	11.811 (outer Ø)	4.055 (width)	2.000 (inner Ø)	7.874 (outer Ø)	2.165 (width)	0.650 (inner Ø)	3.937 (outer Ø)	1.772 (width)
Weight	15 kg / 30 lb		18 kg 40 lb	22 kg 49 lb	15 kg / 30 lb			5 kg / 10 lb			1 kg / 2 lb	
Diameter Range	0.80 - 1.60 mm 0.030 - 1/16 in		1.00 - 1.60 mm 0.040 - 1/16 in		0.60 - 1.60 mm 0.023 - 1/16 in			0.60 - 1.20 mm 0.023 - 0.047 in			0.60 - 1.20 mm 0.023 - 0.047 in	

Drum welding wire packing / Fusto / Fût emballage / Fass Verpackung

Novametal	Nova Drum		Nova Mini Drum	
Dimensions (mm)	515.0 (Ø)		830.0 (height)	
Dimensions (inches)	32.677 (Ø)		20.276 (height)	
Weight	240 to 250 kg - 530 to 550 lb		120 to 125 kg - 275 lb	
Diameter Range	0.80 - 1.60 mm / 0.030 - 1/16 in		0.80 - 1.60 mm / 0.030 - 1/16 in	

TIG welding wire packing / Imballo TIG / TIG emballage / TIG Verpackung

Novametal	Cardboard box A (1)			Cardboard box A (2)			Cardboard box B			Plastic / Cardboard tube	
Dimensions (mm)	1035.0 (length)	47.0 (height)	65.0 (width)	1035.0 (length)	43.0 (height)	58.0 (width)	23876.0 (length)	1016.0 (height)	1397.0 (width)	45 (Ø)	1025 (length)
Dimensions (inches)	40.748 (length)	1.850 (height)	2.56 (width)	40.748 (length)	1.7 (height)	2.283 (width)	940.0 (length)	40.0 (height)	55.0 (width)	40.354 (Ø)	1.772 (height)
Weight	10 kg / 22 lb			5 kg / 10 lb			5 kg / 10 lb			5 kg / 10 lb	
Diameter Range	0.80 - 5.00 mm / 0.030 - 0.197 in			0.80 - 5.00 mm / 0.030 - 0.197 in			0.80 - 5.00 mm / 0.030 - 0.197 in			0.80 - 5.00 mm / 0.030 - 0.197 in	

Submerged Arc Wire Packing / Imballo arco sommerso / Emballage sous flux / Up Verpackung

Novametal	Basket Rim B 450 (acc. to EN ISO 544)		
Dimensions (mm)	308.0 (inner Ø)		415.0 (outer Ø)
Dimensions (inches)	12.126 (inner Ø)		16.339 (outer Ø)
Weight (Kg)	25 kg / 60 lb		
Diameter Range	1.60 - 4.00 mm / 1/16 - 5/32 in		

Mega reels packing

Novametal	Mega Reel			
Dimensions (mm)	520.0 (upper flange)		636.0 (height)	620.0 (bottom flange)
Dimensions (inches)	20.472 (upper flange)		25.039 (height)	24.409 (bottom flange)
Weight (Kg)	300 - 400 kg / 661 - 882 lb			
Diameter Range	1.00 - 1.20 mm / 0.040 - 0.047 in			

Core wire for electrodes' packing / Imballo anime per elettrodi / Emballage pour ames d'électrodes / Verpackung für Kerndraht für Elektrode

Novametal	Wooden box			Wooden box with pitch belt (1)			Wooden box with pitch belt (2)			Wooden box with pitch belt (3)		
Dimensions (mm)	845.0 (length)	480.0 (height)	555.0 (width)	840.0 (length)	642.0 (height)	550.0 (width)	840.0 (length)	642.0 (height)	450.0 (width)	840.0 (length)	642.0 (height)	400.0 (width)
Dimensions (inches)	33.267 (length)	18.897 (height)	21.8504 (width)	33.070 (length)	25.275 (height)	21.653 (width)	33.070 (length)	25.275 (height)	21.653 (width)	33.070 (length)	21.653 (height)	15.748 (width)
Weight	500 - 700 kg / 1102 - 1543 lb			500 - 700 kg / 1102 - 1543 lb			500 - 700 kg / 1102 - 1543 lb			500 - 700 kg / 1102 - 1543 lb		
Diameter Range	1.60 - 5.00 mm / 1/16 in - 0.197 in			1.60 - 5.00 mm / 1/16 in - 0.197 in			1.60 - 5.00 mm / 1/16 in - 0.197 in			1.60 - 5.00 mm / 1/16 in - 0.197 in		